

FILTRU CATALIZATOR
RECE

AUTO-RESTART

**INVERTERE****NORDSTAR****CONFORM SCOP/SEER EN 14825**

Model				CS-51V3A-PB137AE2Q	
BTU				18000	
Alimentare electrica (Faza-V-Hz)				1-220-240/50	
Mod functionare				Racire	Incalzire
Putere evaluata (W)				5100(1900-5500)	5200(2000-5700)
Putere consumata medie (W)				1580(660-1880)	1440(670-1920)
Amperaj mediu (A)				7.2(2.8-8.5)	6.6(2.9-8.7)
SEER/SCOP(W/W)				5.6/A+	3.8/A
Limita temp. ext pe incalzire(°C)				/	-10
Dispozitiv expansiune				Electrovalva de expansiune	
Consum anual evaluat (KW)				293	1879
Deumidificare (L/h)				1,86	
Compressor		Model		ASG133RDNB7AT	
		Tip		Rotativ	
		Brand		Highly	
Unitate interna		Motor		YDK-27-4 A6	
		Tip		AC	
		Ventilator	dia.*lungime (mm)	φ102×707	
		Debit max aer (m3/h)		850	
		Dimensiuni (L*W*H) (mm)		900×292×215	
		Dimensiuni ambalaj (L*W*H) (mm)		983×377×300	
		Masa neta (Kg)		14/17	
		Presiune sonorala (dB/A)		42-46	
Zgomot (dB/A)		52-56			
Unitate externa		Motor		DR-9538-722	
		Tip		cuplaj direct	
		Ventilator	dia.*lungime (mm)	φ415	
		Dimensiuni (L*W*H) (mm)		850×295×605	
		Dimensiuni ambalaj (L*W*H) (mm)		995×415×690	
		Masa Net/Gross (Kg)		45/51	
		Presiune sonora (dB/A)		55	
		Zgomot (dB/A)		65	
Refrigerant tip/masa		R410A/1700g			
Tip dezghet		automat			
Lichid/ Gaz		φ6.35+φ12.7			
Tevi refrigerant		Lungime max. conducta refrigerant(m) /Diferenta max. de nivel (m)		15/5	