



FILTRU CATALIZATOR RECE AUTO-RESTART



**INVERTERE**

**NORDSTAR**

**CONFORM SCOP/SEER EN 14825**

Model		CS-25V3A-MB137AY4T	CS-35V3A-MB137AY4H	CS-51V3A-PB137AE2Q	CS-70V3A-WB137ATF
<b>BTU</b>					<b>24000</b>
Alimentare electrica (Faza-V-Hz)					1-220-240/50
Mod functionare					Racire Incalzire
<b>Putere evaluata (W)</b>					<b>7000(4000-8400) 7000(4000-9000)</b>
Putere consumata medie (W)					2180(900-3360) 2100(900-3360)
Amperaj mediu (A)					10.0(4.2-15.4) 9.6(4.2-15.4)
<b>SEER/SCOP(W/W)</b>					<b>5.6/A+ 4.0/A+</b>
Limita temp. ext pe incalzire(°C)					/ -10
Dispozitiv expansiune					Electrovalva de expansiune
Consum anual evaluat (KW)					402 2579
Deumidificare (L/h)					2,56
Compressor		Model			ATL232SDNC9AUA
		Tip			Rotativ
		Brand			Highly
Unitate interna		Motor			YDK-30-4
		Tip			AC
		Ventilator	dia.*lungime (mm)		φ102×880
		Debit max aer (m3/h)			1050
		Dimensiuni (L*W*H) (mm)			1080×302×220
		Dimensiuni ambalaj (L*W*H) (mm)			1275×392×318
		Masa neta (Kg)			16/20
		Presiune sonora (dB/A)			42-48
Zgomot (dB/A)			52-58		
Unitate externa		Motor			MDR-9538-901M
		Tip			cuplaj direct
		Ventilator	dia.*lungime (mm)		φ460×180
		Dimensiuni (L*W*H) (mm)			900×330×835
		Dimensiuni ambalaj (L*W*H) (mm)			1030×440×960
		Masa Net/Gross (Kg)			65/80
		Presiune sonora (dB/A)			58
		Zgomot (dB/A)			68
Refrigerant tip/masa			R410A/2400g		
Tip dezghet			automat		
Tevi refrigerant		Lichid/ Gaz			φ9.52 + φ15.88
		Lungime max. conducta refrigerent(m) /Diferenta max. de nivel (m)			15/5