

FILTRU CATALIZATOR  
RECE

AUTO-RESTART

**INVERTERE****NORDSTAR****CONFORM SCOP/SEER EN 14825**

<b>Model</b>		<b>CS-25V3A-MB137AY4T</b>				
<b>BTU</b>		<b>9000</b>				
Alimentare electrica (Faza-V-Hz)		1-220-240/50				
Mod functionare		Racire	Incalzire			
<b>Putere evaluata (W)</b>		<b>2500(1500-3300)</b>	<b>2600(1300-3400)</b>			
Putere consumata medie (W)		775(380-1200)	720(390-1200)			
Amperaj mediu (A)		3.5(1.6-5.4)	3.3(1.7-5.5)			
<b>SEER/SCOP(W/W)</b>		<b>5.6/A+</b>	<b>3.8/A</b>			
Limita temp. ext pe incalzire(°C)		/	-10			
Dispozitiv expansiune		Capilar				
Consum anual evaluat (KW)		156	884			
Deumidificare (L/h)		0,95				
Compressor		Model	5RS092ZJB21			
		Tip	Rotativ			
		Brand	Panasonic			
Unitate interna		Motor	Model	YDK-16-4G		
		Tip	AC			
		Ventilator	dia.*lungime (mm)	φ98×622		
		Debit max aer (m3/h)	500			
		Dimensiuni (L*W*H) (mm)	800×280×190			
		Dimensiuni ambalaj (L*W*H) (mm)	865×358×275			
		Masa neta (Kg)	10/12			
		Presiune sonora (dB/A)	30-38			
Zgomot (dB/A)	40-48					
Unitate externa		Motor	Model	D-280-25-8A\280-315V		
		Tip	cuplaj direct			
		Ventilator	dia.*lungime (mm)	Φ408×134		
		Dimensiuni (L*W*H) (mm)	715×235×540			
		Dimensiuni ambalaj (L*W*H) (mm)	851×335×600			
		Masa Net/Gross (Kg)	30/32			
		Presiune sonora (dB/A)	53			
		Zgomot (dB/A)	63			
Refrigerant tip/masa	R410A/770g					
Tip dezghet	automat					
Tevi refrigerant		Lichid/ Gaz	φ6.35+φ9.52			
		Lungime max. conducta refrigerant(m) /Diferenta max. de nivel (m)	15/5			